


**ZKLN90150-2Z-XL**

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...-2Z, double direction, gap seals on
both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	90 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,008 mm	Bore diameter lower tolerance
D	150 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,015 mm	Outside diameter lower tolerance
B	55 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	149.000 N	Basic dynamic load rating, axial
C _{0a}	395.000 N	Basic static load rating, axial
C _{ua}	21.900 N	Fatigue load limit, axial
n _G Grease	3.500 1/min	Limiting speed for grease lubrication
n _g	2.300 1/min	Thermally safe operating speed
M _R	2,3 Nm	Bearing frictional torque
≈m	3,703 kg	Masa



Mounting dimensions

D _a max	138 mm	Maximum diameter of housing
d _a min	116 mm	Minimum diameter shaft

Dimensions

d ₁	120 mm	Rib diameter inner ring
r _{min}	0,6 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
α	60 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	1.700 N/μm	Rigidity axial
c _{kL}	4.400 Nm/mrad	Tilting rigidity
M _m	59,9 kg*cm2	Mass moment of inertia
	3 μm	Axial runout
	ZMA90/130	Recommended INA precision locknut for radial locking
	AM90	Recommended INA precision locknut for axial locking
M _A	200 Nm	Tightening torque for the recommended INA precision locknut
	22.731 N	Required locknut force axial



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne